

SAFETY DATA SHEET

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: BODY PREP SOLVENT
 PRODUCT NO: S-52
 RECOMMENDED USE: Automotive Tar Remover

COMPANY: Appearance Materials Inc
 58 Westbrook Industrial Park RD
 Westbrook, CT 06498
 USA
 860-399-6275

EMERGENCY TELEPHONE NUMBER: Appearance Materials 86-399-6275
 CHEMTREC . 800-424-9300

SECTION 2: HAZARDS IDENTIFICATION**Danger**

Causes skin burns and eye damage. Harmful if inhaled. May cause drowsiness or dizziness. May cause respiratory irritation. May cause damage to organs (liver, kidney, central nervous system) through prolonged or repeated exposure. Suspected of causing cancer. May be fatal if swallowed and enters airways. Flammable liquid and vapor.

Wear protective gloves and eye protection. Do not breathe vapors. Use only outdoors or in a well-ventilated area. Wash thoroughly after handling. Do not eat drink or smoke when using this product. Keep away from heat and flames. Keep container tightly closed. Use explosion proof equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a doctor.

If on skin: Wash with plenty of water. Take off immediately all contaminated clothing and wash it before reuse. Immediately call a doctor.

If swallowed: Rinse mouth. Immediately call a doctor. Do NOT induce vomiting.

If inhaled: Remove person to fresh air and keep comfortable for breathing. Immediately call a doctor.

If exposed or concerned: Get medical advice.

Get medical advice if you feel unwell.

In case of fire: Use foam/carbon dioxide/regular dry chemical/water to extinguish.

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Keep cool.

Dispose of unused product and container in accordance with federal, state and local regulations.

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

| INGREDIENT | CAS # | WEIGHT % |
|--------------------------|-----------|----------|
| Mineral spirits, regular | 8052-41-3 | 70-80** |
| Xylene | 1330-20-7 | 20-30** |

*Identity of this ingredient is a trade secret

**Exact percentage of this ingredient is a trade secret

SECTION 4: FIRST AID MEASURES

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a doctor.

If on skin: Wash with plenty of water. Take off immediately all contaminated clothing and wash it before reuse. Immediately call a doctor.

If swallowed: Rinse mouth. Immediately call a doctor. Do NOT induce vomiting.

If inhaled: Remove person to fresh air and keep comfortable for breathing. Immediately call a doctor.

SECTION 5: FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Use water spray, dry chemical, carbon dioxide or "alcohol" foam.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Combustion may produce noxious and irritating gases which will require fresh air source in fire fighting.

SPECIAL FIRE FIGHTING PROCEDURES: Firefighters should be equipped with self-contained breathing apparatus and turnout gear as a general precaution.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Use personal protective equipment; see Section 8.

Keep product from entering storm sewers and ditches that may lead to waterways.

Stop spill at source; dike and contain large spills and transfer to recovery container. Use absorbent for small spills and containerize.

See Section 13 for disposal.

SECTION 7: HANDLING AND STORAGE

Handle according to good manufacturing and warehousing practices. Avoid contact with eyes, skin and clothing.

Store indoors between 40F/4C and 100F/38C

Use product only for intended use. Follow label directions.

Wash hands after handling.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

| INGREDIENT | CAS # | OSHA PEL (ppm or *mg.M ³) +=skin, c=ceiling | ACGIH TWA (ppm or *mg.M ³) +=skin, c=ceiling |
|-------------------------|-----------|---|--|
| Mineral Spirits Regular | 8052-41-3 | 500 | 100 |
| Xylene | 1330-20-7 | 500 | 100 |

EYES: Wear eye protection (i.e. chemical safety glasses with side shields or goggles). Contact lenses should not be worn.

SKIN: Chemical resistant clothing (i.e. gloves) is recommended.

RESPIRATORY PROTECTION: Not expected to be needed. Where over-exposure through inhalation may occur from use, approved respiratory protection equipment is recommended.

VENTILATION: Local exhaust or general room ventilation is normally adequate.

OTHER PROTECTIVE EQUIPMENT: Emergency eye wash station is recommended.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Clear liquid
 ODOR: Petroleum odor
 ODOR THRESHOLD: NA
 pH: NA
 MELTING/FREEZING POINT: NA
 BOILING POINT: APPROX NA
 BOILING RANGE: 300-400F
 FLASH POINT (CC): 105F
 EVAPORATION RATE: 0.11 n butyl acetate
 FLAMMABILITY: Flammable
 UPPER/LOWER FLAMMABILITY LIMITS: NA
 UPPER/LOWER EXPLOSIVE LIMITS: 6%/1% (Minersal spirits)
 VAPOR PRESSURE: 0.62 mmHg @ 68F
 VAPOR DENSITY: 4.9 (Air = 1)
 RELATIVE DENSITY: 6.4 LB/GAL
 SOLUBILITY: Soluble in hydrocarbon solvents Not soluble in water
 PARTITION COEFFICIENT: N-OCTANOL/WATER: NA
 AUTO-IGNITION TEMPERATURE: NA
 DECOMPOSITION TEMPERATURE: NA
 VISCOSITY: Water thin

SECTION 10: STABILITY AND REACTIVITY

REACTIVITY: Stable
 CHEMICAL STABILITY: Stable
 POSSIBILITY OF HAZARDOUS REACTIONS: Low.
 INCOMPATIBLE MATERIALS: Avoid oxidizers and reducers.
 HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide and other gases.

SECTION 11: TOXICOLOGICAL INFORMATION

Naphthalene is listed as carcinogenic by IARC and NTP
 This product contains no other ingredients at or about 0.1% that are listed by NTP, IARC, or OSHA as carcinogens.
 Ingredient(s) in this product are harmful to the fetus.

SECTION 12: ECOLOGICAL INFORMATION

Ecological data for this chemical mixture is not available.

SECTION 13: DISPOSAL CONSIDERATIONS

Dispose of in accordance with federal, state and local environmental regulations.

SECTION 14: TRANSPORT INFORMATION

| Regulatory information | UN number | Proper shipping name | Class | Packing group | Label | Additional information |
|------------------------|-----------|------------------------------------|-------|---------------|-------|------------------------|
| DOT | NA | Not regulated when shipped by land | NA | NA | - | |

SECTION 15: REGULATORY INFORMATION

RTK Ingredients : Mineral spirits, regular (8052-41-3), Xylene (1330-20-7)

SECTION 16: OTHER INFORMATION

NFPA 704

HAZARD RATING

| | | |
|------------|--------------|-----|
| 4=Severe | H=Health | H=2 |
| 3=Serious | F=Fire | F=2 |
| 2=Moderate | R=Reactivity | R=0 |
| 1=Slight | | |
| 0=Minimal | | |

Prepared: November 9, 2015

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for the safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information related only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Neither this data sheet nor any statement contained herein grants or extends any license, expressed or implied, in connection with patents issued or pending which maybe the property of the manufacturer or others. The information in this data sheet has been assembled by the manufacturer or his agent based on its own studies and on the work of others. Neither the manufacturer nor his agent makes any warranty, expressed or implied, as to the accuracy, completeness, or adequacy of the information contained herein. Neither the manufacturer nor his agent shall be held liable (regardless of fault) to the vendee, the vendee's employees or anyone for any direct, special or consequential damages arising out of or in connection with the accuracy, completeness, adequacy or furnishing of such information. Data is supplied for use only in connection with occupational safety and health.